

Mineral packing

# LATTY HEPHAISTOS 2000 G

insulating bolster up to 850°C

## EXPANSION JOINT, HIGH-TEMPERATURE APPLICATIONS AND INSULATION

- HIGH THERMAL INSULATION CAPACITY
- GOOD SOUND INSULATION PROPERTIES



### OPERATING PARAMETERS (NOT ASSOCIATED)

Temperature : 0 °C 850°C  
pH : 2 - 13

### COMPOSITION

Flexible sleeve braided with glass fibres, treated for high-temperature resistance, reinforced with nickel-chrome alloy yarns, around a core containing high-temperature corded glass fibres and natural fibres. Outstanding thermal insulation capacity, high resistance to thermal shocks, good sound insulation properties.

### TYPES OF INDUSTRIES



### FLUIDS

High-temperature sealing

Item	Dimensions	Description
61167	Ø 5 mm	350 m
61168	Ø 6 mm	250 m
61169	Ø 8 mm	200 m
61170	Ø 10 mm	200 m
61171	Ø 12 mm	125 m
61172	Ø 15 mm	75 m
61173	Ø 20 mm	50 m
61174	Ø 25 mm	40 m
61166	Ø 30 mm	25 m
61175	Ø 50 mm	15 m