

Mineral packing

# LATTY HEPHAISTOS 2000 T

very high fire resistance

## HIGH-TEMPERATURE APPLICATIONS

- FOR OVEN DOORS, BOILERS, BURNERS, ETC.
- VARIOUS INSULATIONS



### OPERATING PARAMETERS (NOT ASSOCIATED)

Pressure : 0 to < 100 bar  
Temperature : 0 °C to 850°C  
pH : 2 - 13

### COMPOSITION

Braided packing made of high-temperature treated glass fibres reinforced with nickel-chrome wires and impregnated with a mica-based mix.

### TYPES OF INDUSTRIES



### FLUIDS

High-temperature sealing



| Item   | Dimensions | Description |
|--------|------------|-------------|
| 60589  | □ 6 mm     | 20 m        |
| 60590  | □ 8 mm     | 15 m        |
| 60591  | □ 10 mm    | 12 m        |
| 60592  | □ 12 mm    | 11 m        |
| 60593* | □ 12,7 mm  | 11 m        |
| 60594  | □ 14 mm    | 10 m        |
| 60595  | □ 16 mm    | 10 m        |
| 60596  | □ 20 mm    | 10 m        |

\* Made to order

The maximum temperature, pressure and speed parameters specified in this document can not be combined.

0157