

Carbon Aramid

LATTYCARB 96

A carbon sheet supple and easy to cut for static sealing

GENERAL-PURPOSE ARAMID/CARBON, GRAPHITED ON BOTH FACES

- ANTI-ADHESIVE TREATMENT ON BOTH FACES
- IMPROVED RESISTANCE OF THE GASKET AT HIGH TEMPERATURES RESULTING FROM THE PRESENCE OF ELASTOMER REINFORCED BY CARBON FIBRES
- FOR HIGH-PRESSURE APPLICATIONS



OPERATING PARAMETERS (NOT ASSOCIATED)

Pressure : 0 to 130 bar
Temperature : 0 °C to 450°C

COMPOSITION

Gasket material made of selected carbon and mineral fibres bonded with a mix of synthetic elastomers, compressed to obtain sheet material. Anti-stick treatment on both faces.

TYPES OF INDUSTRIES



FLUIDS

High-performance material which meets most applications: steam, high-pressure applications, all hydrocarbons.

GUIDELINES, STANDARDS AND APPROVALS



Item	Dimensions	Description
67475	0,5 mm	1,5 m x 2 m
46630	0,5 mm	1 m x 1,5 m
69766	1 mm	1 m x 1,5 m
43948	1 mm	1 m x 1,5 m
47859	1 mm	1,5 m x 2 m
69767	1,5 mm	1 m x 1,5 m
43949	1,5 mm	1 m x 1,5 m
48651	1,5 mm	1,5 m x 2 m
43950	2 mm	1 m x 1,5 m
47860	2 mm	1,5 m x 2 m
50172	2 mm	1 m x 1,5 m
43951	3 mm	1 m x 1,5 m
47068	3 mm	1,5 m x 2 m
51421	3 mm	1,5 m x 1,5 m