

Carbon Aramid

LATTYCARB 965

A carbon sheet supple and easy to cut for static sealing

SHEET MATERIAL REINFORCED WITH AN INTERNAL STEEL WIRE MESH.

- FLEXIBLE GASKET MATERIAL, EASY TO CUT



OPERATING PARAMETERS (NOT ASSOCIATED)

Pressure : 0 to 150 bar
 Temperature : 0 °C to 450°C

COMPOSITION

Gasket material made of selected carbon and mineral fibres bonded with a mix of synthetic elastomers, compressed to obtain sheet material. The sheet material is reinforced with an internal steel wire mesh. A special graphite coating, applied on both faces, makes disassembly operations extremely fast and minimises flange corrosion.

TYPES OF INDUSTRIES



FLUIDS

High-performance material which meets most applications: steam, high-pressure applications, all hydrocarbons.

Item	Dimensions	Description
43961	1 mm	1 m x 1,5 m
49194	1 mm	1,5 m x 2 m
43962	1,5 mm	1 m x 1,5 m
49512	1,5 mm	1,5 m x 2 m
43963	2 mm	1 m x 1,5 m
47253	2 mm	1,5 m x 2 m
43964	3 mm	1 m x 1,5 m
47861	3 mm	1,5 m x 2 m