


Vegetable packing

LATTYFLON 1779

Anti-rot packing

VEGETABLE PACKING FOR ROTARY UNIT APPLICATIONS

- IMPREGNATED WITH A MIX OF PTFE AND INERT LUBRICANT DURING BRAIDING OPERATION.



OPERATING PARAMETERS (NOT ASSOCIATED)

Pressure : 0 to 400 bar
Temperature : -40 °C to 120°C
Speed : < 15 m/s
pH : 4 - 11

COMPOSITION

Packing made of anti-rot high-quality ramie yarns, impregnated with a mix of PTFE and inert lubricant during braiding operation.

TYPES OF INDUSTRIES



FLUIDS

All types of fluids

Item	Dimensions	Description
00100116*	□ 4 mm	35 m / 0,77 Kg
00100118	□ 6 mm	20 m / 1,00 Kg
33980*	□ 6,35 mm	20 m / 1,12 Kg
00100119	□ 8 mm	15 m / 1,28 Kg
00100844	□ 9,5 mm	12 m / 1,44 Kg
00100120	□ 10 mm	12 m / 1,60 Kg
00100122	□ 12 mm	11 m / 2,07 Kg
00100123	□ 12,7 mm	11 m / 2,31 Kg
00100124	□ 14 mm	10 m / 2,55 Kg
00100125	□ 16 mm	10 m / 3,40 Kg
00100126*	□ 18 mm	10 m / 4,20 Kg
00100127	□ 20 mm	10 m / 5,30 Kg
00100128*	□ 22 mm	10 m / 5,8 Kg

* Made to order

The maximum temperature, pressure and speed parameters specified in this document can not be combined.

0121

DYNAMIC SEALING SOLUTIONS: ROTARY UNITS
MECHANICAL SEAL