


Synthetic packing

# LATTYFLON 2790 AL

Packing for drinking water for dynamic sealing

## PACKING FOR DRINKING WATER FOR DYNAMIC SEALING

- LATTY-EXCLUSIVE «FILCOAT»-PROCESS
- LIMITATIONS WITH ACIDS AND STRONG BASES



### OPERATING PARAMETERS (NOT ASSOCIATED)

Pressure : 0 to 100 bar  
 Temperature : -50 °C to 260°C  
 Speed : < 15 m/s  
 pH : 1 - 13

### COMPOSITION

Packing made of special polyacrylic yarns, each single yarn being impregnated with PTFE using our exclusive «Filcoat»-process, then re-impregnated during braiding operation with a mix of PTFE and food-grade silicon lubricant.

### TYPES OF INDUSTRIES



### FLUIDS

All types of fluids

### GUIDELINES, STANDARDS AND APPROVALS



Item	Dimensions	Description
63520*	□ 4 mm	35 m / 0,84Kg
63521*	□ 5 mm	25 m / 0,81 Kg
37964	□ 6 mm	20 m / 0,96 Kg
34259*	□ 6,35 mm	20 m / 1,05 Kg
34260	□ 8 mm	15 m / 1,25 Kg
36959	□ 9,5 mm	12 m / 1,44 Kg
34261	□ 10 mm	12 m / 1,56 Kg
34262	□ 11 mm	11 m / 1,72 Kg
34263	□ 12 mm	11 m / 2,10 Kg
34264	□ 12,7 mm	11 m / 2,32 Kg
40845	□ 14 mm	10 m / 2,53 Kg
34265	□ 16 mm	10 m / 3,30 Kg
37729	□ 19 mm	10 m / 4,60 Kg
40847	□ 20 mm	10 m / 5,20 Kg

\* Made to order

The maximum temperature, pressure and speed parameters specified in this document can not be combined.

