


Synthetic packing

# LATTYFLON 2790

Packing for Food Industry (EC 1935/2004) in dynamic sealing

**PACKING FOR FOOD INDUSTRY (EC 1935/2004)**

- FOR ROTARY UNITS
- LATTY-EXCLUSIVE «FILCOAT»-PROCESS



**OPERATING PARAMETERS**  
(NOT ASSOCIATED)

Pressure : 0 to 100 bar  
 Temperature : -50 °C to 260°C  
 Speed : < 15 m/s  
 pH : 1 - 13

**COMPOSITION**

Packing made of special polyacrylic yarns, each single yarn being impregnated with PTFE using our exclusive Filcoat-process, then re-impregnated during braiding operation with a mix of PTFE and inert lubricant.

**TYPES OF INDUSTRIES**



**FLUIDS**

All types of fluids

**GUIDELINES, STANDARDS AND APPROVALS (ON REQUEST)**



Item	Dimensions	Description
00101431	□ 6 mm	20 m / 0,99 Kg
00101458*	□ 6,35 mm	20 m / 1,11 Kg
00101430	□ 8 mm	15 m / 1,35 Kg
00101422	□ 9,5 mm	12 m / 1,50 Kg
00101435	□ 10 mm	12 m / 1,73 Kg
00101440	□ 11 mm	11 m / 1,92 Kg
00101423	□ 12 mm	11 m / 2,25 Kg
00101410	□ 12,7 mm	11 m / 2,53 Kg
00101424	□ 14 mm	10 m / 2,80 Kg
00101433	□ 16 mm	10 m / 3,60 Kg
00101442	□ 19 mm	10 m / 4,70 Kg
00101434	□ 20 mm	10 m / 5,20 Kg
00101443	□ 22 mm	10 m / 6,13 Kg
00101444	□ 25,4 mm	10 m / 8,06 Kg

\* Made to order

The maximum temperature, pressure and speed parameters specified in this document can not be combined.