


PTFE packing

# LATTYFLON 3206 AL

PTFE packing

## FOOD COMPATIBILITY IN DYNAMIC APPLICATIONS, WITH CHEMICAL INERTNESS OF PTFE.

- VERY LOW FRICTION COEFFICIENT
- EASY STEM OPERATION



### OPERATING PARAMETERS (NOT ASSOCIATED)

Pressure : 0 to 100 bar  
 Temperature : -200 °C to 280 °C  
 Speed : < 10 m/s  
 pH : 0 - 14

### COMPOSITION

Packing made of 100% PTFE silk yarns and lubricant with food-grade silicon.

### TYPES OF INDUSTRIES



### FLUIDS

Chemically aggressive fluids

### GUIDELINES, STANDARDS AND APPROVALS



Item	Dimensions	Description
33746	□ 5 mm	25 m / 1,00 Kg
33747	□ 6 mm	20 m / 1,28 Kg
37194*	□ 6,35 mm	20 m / 1,14 Kg
33748	□ 8 mm	15 m / 1,56 Kg
33749	□ 10 mm	12 m / 1,86 Kg
33750	□ 12 mm	11 m / 2,48 Kg
33752	□ 14 mm	10 m / 3,25 Kg
33753	□ 16 mm	10 m / 4,10 Kg
33754*	□ 18 mm	10 m / 5,30 Kg
33755	□ 19 mm	10 m / 6,20 Kg
33756	□ 20 mm	10 m / 6,40 Kg

\* Made to order

The maximum temperature, pressure and speed parameters specified in this document can not be combined.

0105

DYNAMIC SEALING SOLUTIONS: ROTARY UNITS  
MECHANICAL SEAL