


PTFE packing

LATTYFLON 3206 SO

Oxygen-compatible packing

PRODUCTS DEDICATED TO OXYGEN-TYPE APPLICATIONS.

- VERY LOW FRICTION COEFFICIENT
- PERFECT CHEMICAL INERTNESS



OPERATING PARAMETERS (NOT ASSOCIATED)

Pressure : 0 to 300 bar
 Temperature : -200 °C to 300°C
 Speed : < 5 m/s
 pH : 0 - 14

COMPOSITION

Packing made of 100% PTFE silk yarns, each single yarn being impregnated with PTFE, then treated to ensure perfect oxygen compatibility.

TYPES OF INDUSTRIES



FLUIDS

All types of fluids, except abrasive fluids

GUIDELINES, STANDARDS AND APPROVALS



Item	Dimensions	Description
31449	□ 5 mm	25 m / 0,95 Kg
31353	□ 6 mm	20 m / 1,06 Kg
31414	□ 8 mm	15 m / 1,45 Kg
33275	□ 10 mm	12 m / 1,72 Kg
33276	□ 12 mm	11 m / 2,30 Kg
33277	□ 14 mm	10 m / 3,00 Kg
31584	□ 16 mm	10 m / 4,00 Kg
30484*	□ 18 mm	10 m / 5,00 Kg
30568	□ 19 mm	10 m / 5,10 Kg
31667	□ 20 mm	10 m / 5,60 Kg

* Made to order

The maximum temperature, pressure and speed parameters specified in this document can not be combined.

