

PTFE packing

LATTYFLON 3207

Packing suitable for aggressive environments in dynamic sealing

FOR CHEMICALLY AGGRESSIVE FLUIDS

- GRAPHITED PTFE PACKING
- DEDICATED TO APPLICATIONS ON ROTARY PUMPS



OPERATING PARAMETERS (NOT ASSOCIATED)

Pressure : 0 to 80 bar
 Temperature : -200 °C to 250 °C
 Speed : < 20 m/s
 pH : 0 - 14

COMPOSITION

Packing made of 100% PTFE silk yarns, pre-treated with continuous graphite impregnation to the core, then re-impregnated with a silicon lubricant.

TYPES OF INDUSTRIES



FLUIDS

All types of fluids, except abrasive fluids

Item	Dimensions	Description
42957	□ 6 mm	20 m / 1,16 Kg
42959	□ 8 mm	15 m / 1,47 Kg
42960	□ 9,5 mm	12 m / 1,76 Kg
42961	□ 10 mm	12 m / 1,89 Kg
55981	□ 11 mm	11 m / 1,98 Kg
42962	□ 12 mm	11 m / 2,47 Kg
42963	□ 12,7 mm	11 m / 2,80Kg
42964	□ 14 mm	10 m / 3,2 Kg
55982	□ 15 mm	10 m / 3,71 Kg
42965	□ 16 mm	10 m / 4,1 Kg
46924	□ 18 mm	10 m / 5,25 Kg
45219	□ 19 mm	10 m / 6,05 Kg
43003	□ 20 mm	10 m / 6,4 Kg
46925	□ 22 mm	10 m / 7,8 Kg
44116	□ 25,4 mm	11 m / 10,9 Kg