

PTFE packing

LATTYFLON 4308

Packing for applications on rotary pumps with chemically aggressive fluids

VERY LOW FRICTION COEFFICIENT

- GRAPHITED PTFE PACKING, DEDICATED TO APPLICATIONS ON ROTARY PUMPS WITH CHEMICALLY AGGRESSIVE FLUIDS
- OUTSTANDING HEAT TRANSFER COEFFICIENT
- GOOD ELECTRICAL CONDUCTOR, NO BUILD-UP OF STATIC CHARGE



OPERATING PARAMETERS (NOT ASSOCIATED)

Pressure : 0 to 110 bar
 Temperature : -200 °C to 300°C
 Speed : < 26 m/s
 pH : 0 - 14

COMPOSITION

Packing made of 100% PTFE silk yarns, pre-treated with continuous graphite impregnation to the core, then re-impregnated with a silicon lubricant.

TYPES OF INDUSTRIES



FLUIDS

All types of fluids, except abrasive fluids

Item	Dimensions	Description
00101655*	□ 4 mm	35 m / 0,93 Kg
00101626	□ 5 mm	25 m / 1,05 Kg
00101581	□ 6 mm	20 m / 1,16 Kg
00101663*	□ 6,35 mm	20 m / 1,3 Kg
00101579	□ 8 mm	15 m / 1,47 Kg
00101617	□ 9,5 mm	12 m / 1,76 Kg
00101580	□ 10 mm	12 m / 1,89 Kg
00101583*	□ 11 mm	11 m / 2,00 Kg
00101582	□ 12 mm	11 m / 2,47 Kg
00101584	□ 12,7 mm	11 m / 2,8 Kg
00101652	□ 14 mm	10 m / 3,2 Kg
00101634	□ 15 mm	10 m / 3,71 Kg
00101616	□ 16 mm	10 m / 4,10 Kg
00101685	□ 18 mm	10 m / 5,25 Kg
00101653	□ 19 mm	10 m / 6,05 Kg
00101654	□ 20 mm	10 m / 6,40 Kg
00101635	□ 22 mm	10 m / 7,80 Kg
00101632	□ 25,4 mm	10 m / 10 Kg

* Made to order
 The maximum temperature, pressure and speed parameters specified in this document can not be combined.

