


Aramid packing

LATTYFLON 4788

Aramid packing: the first one and still n°1!

OUTSTANDING RESISTANCE WITH ABRASIVE FLUIDS

- LATTY-EXCLUSIVE «FILCOAT»-PROCESS
- UNMATCHED MECHANICAL RESISTANCE
- SILICONE-FREE PACKING



OPERATING PARAMETERS (NOT ASSOCIATED)

Pressure : 0 to 200 bar
 Temperature : -200 °C to 300°C
 Speed : < 25 m/s
 pH : 2 - 13

COMPOSITION

Packing made of continuous 100% aramid fibres, each single yarn being impregnated with PTFE using our exclusive «Filcoat»-process, then re-impregnated with a mix of PTFE and inert food-quality lubricant during braiding operation.

TYPES OF INDUSTRIES



FLUIDS

Slurries fluids

GUIDELINES, STANDARDS AND APPROVALS



Item	Dimensions	Description
00100276	□ 5 mm	25 m / 0,85 Kg
00100277	□ 6 mm	20 m / 1,00 Kg
00101153*	□ 6,35 mm	20 m / 1,12 Kg
00100278*	□ 7 mm	20 m / 1,02 Kg
00100279	□ 8 mm	15 m / 1,33 Kg
00100280	□ 9,5 mm	12 m / 1,55 Kg
00100281	□ 10 mm	12 m / 1,70 Kg
00100282*	□ 11 mm	12 m / 1,85 Kg
00100283	□ 12 mm	11 m / 2,20 Kg
00100284	□ 12,7 mm	11 m / 2,45 Kg
00100285	□ 14 mm	10 m / 2,75 Kg
00100286	□ 15 mm	10 m / 3,20 Kg
00100287	□ 16 mm	10 m / 3,62 Kg
00100288	□ 18 mm	10 m / 4,44 Kg
00100289	□ 19 mm	10 m / 4,94 Kg
00100290	□ 20 mm	10 m / 5,47 Kg
00100291	□ 22 mm	10 m / 6,66 Kg
00100292	□ 25,4 mm	10 m / 9,00 Kg

* Made to order

The maximum temperature, pressure and speed parameters specified in this document can not be combined.

