


Aramid packing

LATTYFLON 5790 S

Packing for Food Industry (EC 1935/2004)

PACKING FOR FOOD INDUSTRY (EC 1935/2004)

- DRY PACKING WITHOUT IMPREGNATION DURING BRAIDING OPERATION
- PACKING FOR MIXERS, CONVEYORS, ETC.
- IMPREGNATED WITH SILICONE-FREE LUBRICANT
- LATTY-EXCLUSIVE «FILCOAT»-PROCESS



OPERATING PARAMETERS (NOT ASSOCIATED)

Pressure : 0 to 100 bar
 Temperature : -50 °C to 260°C
 Speed : < 20 m/s
 pH : 2 - 13

COMPOSITION

Outstanding resistance to wear in rotation. Very high mechanical resistance, whilst being less abrasive. The yarns are impregnated with silicone-free lubricant to the core prior to braiding using our patented «FILCOAT» process. Specific lubricant with outstanding sliding properties. Enhances abrasion resistance. The low friction coefficient ensures significant energy savings.

TYPES OF INDUSTRIES



FLUIDS

Slurries fluids

GUIDELINES, STANDARDS AND APPROVALS (ON REQUEST)



Made to order Consultarnos

The maximum temperature, pressure and speed parameters specified in this document can not be combined.

0101

DYNAMIC SEALING SOLUTIONS: ROTARY UNITS
MECHANICAL SEAL