


Aramid packing

LATTYFLON 5790

Dynamic sealing: packing for Food Industry (EC 1935/2004)

GOOD WEAR RESISTANCE

- GENTLE ON SLEEVE OR SHAFT AS A RESULT OF THE SYNTHETIC YARNS OF THE PACKING
- IMPREGNATED WITH SILICONE-FREE LUBRICANT
- PACKING FOR HIGH-SPEED APPLICATIONS
- LATTY-EXCLUSIVE «FILCOAT»-PROCESS



OPERATING PARAMETERS (NOT ASSOCIATED)

Pressure : 0 to 100 bar
Temperature : -50 °C to 260°C
Speed : < 20 m/s
pH : 2 - 13

COMPOSITION

Outstanding resistance to wear in rotation. Very high mechanical resistance, whilst being less abrasive. The yarns are impregnated with silicone-free lubricant to the core prior to braiding using our patented «FILCOAT» process. Specific lubricant with outstanding sliding properties. Enhances abrasion resistance. The low friction coefficient ensures significant energy savings.

TYPES OF INDUSTRIES



FLUIDS

Slurries fluids

GUIDELINES, STANDARDS AND APPROVALS (ON REQUEST)



Item	Dimensions	Description
80361	□ 6 mm	12 m / 0,69 Kg
80362	□ 8 mm	12 m / 1,15 Kg
80363	□ 10 mm	9 m / 1,35 Kg
80364	□ 12 mm	9 m / 1,94 Kg
80365	□ 12,7 mm	9 m / 2,18 Kg
80366	□ 14 mm	6 m / 1,76 Kg
80367	□ 16 mm	6 m / 2,3 Kg
80369	□ 20 mm	6 m / 3,6 Kg
900001145*	□ 18 mm	6 m / 2,6 Kg
900002860*	□ 22 mm	6 m / 3,9 Kg
900002861*	□ 25,4 mm	6 m / 5,2 Kg

* Made to order

The maximum temperature, pressure and speed parameters specified in this document can not be combined.

