

Synthetic packing

LATTYFLON 7188

Packing made of compound yarn, impregnated with a mix of PTFE and inert lubricant for dynamic sealing

HIGH-PERFORMANCE SYNTHETIC PACKING FOR SLURRIES

- REDUCED RUNNING-IN TIME. SILICONE-FREE LUBRICANT
- REDUCED RETIGHTENING OPERATIONS
- PACKING SOLD ONLY BY THE METRE OR PREFORMED LENGTH



OPERATING PARAMETERS (NOT ASSOCIATED)

Pressure : 0 to 200 bar
Temperature : -200 °C to 300°C
Speed : < 20 m/s
pH : 1 - 13

COMPOSITION

Packing made of phenolic compound yarns impregnated during braiding operation with a mix of PTFE and inert lubricant. Very good mechanical characteristics combining both suppleness and robustness.

TYPES OF INDUSTRIES



FLUIDS

All industries using abrasive fluids, slurries.

Item	Dimensions	Description
00101727	□ 6 mm	20 m / 1,10 Kg
25735*	□ 6,35 mm	20 m / 1,23 Kg
00101728	□ 8 mm	15 m / 1,43 Kg
00101729	□ 9,5 mm	12 m / 1,62 Kg
00101730	□ 10 mm	12 m / 1,72 Kg
25622*	□ 11 mm	11 m / 2,04Kg
00101731	□ 12 mm	11 m / 2,40 Kg
00101732	□ 12,7 mm	11 m / 2,62 Kg
22222	□ 14 mm	10 m / 2,92 Kg
00101734	□ 16 mm	10 m / 3,92 Kg
00101742*	□ 18 mm	10 m / 4,75 Kg
00101735*	□ 19 mm	10 m / 5,12 Kg
00101736	□ 20 mm	10 m / 5,79 Kg
00101737*	□ 22 mm	10 m / 6,87 Kg
22223*	□ 25,4 mm	10 m / 8,68 Kg

* Made to order
The maximum temperature, pressure and speed parameters specified in this document can not be combined.

