

Synthetic packing

LATTYCORE 7189 G

Packing specially dedicated to slurries

FLEXIBLE, ROBUST PACKING WITH EXCELLENT ELASTIC RECOVERY PROPERTIES

- LITTLE RETIGHTENING REQUIRED AFTER INSTALLATION EASY CUTTING, LOW HEAT
- CAN BE USED WITHOUT A LANTERN RING
- PACKING SOLD ONLY BY THE METRE OR PREFORMED LENGTH

OPERATING PARAMETERS
(NOT ASSOCIATED)

Pressure : 0 to 200 bar
 Temperature : 0 °C to 260°C
 Speed : < 20 m/s
 pH : 1 - 13

COMPOSITION

Made on the edges of phenolic composite yarns, each single yarn being impregnated with PTFE using our exclusive Filcoat-process, and of polyacrylic yarns on friction faces.

TYPES OF INDUSTRIES



FLUIDS

Slurries fluids

Item	Dimensions	Description
900015133	□ 6 mm	10 m / 0,89 Kg
900013745	□ 8 mm	15 m / 1,4 Kg
900015447	□ 9,5 mm	10 m / 1,0 Kg
900013746	□ 10 mm	12 m / 1,8 Kg
900013643	□ 12 mm	10 m / 1,7 Kg
900013747	□ 12,7 mm	11 m / 2,0Kg
900013728	□ 14 mm	10 m / 2,3 Kg
900013552	□ 16 mm	10 m / 2,9 Kg
900015448	□ 18 mm	10 m / 3,7 Kg
900013560	□ 19 mm	10 m / 4,2 Kg
900014501	□ 20 mm	10 m / 4,6 Kg
900017539	□ 22 mm	10 m / 6,3 Kg
900013642	□ 25,4 mm	10 m / 7,4 Kg