

PTFE

LATTYFLON UNISEAL

PTFE LATTYflon UNISEAL gasket: continuous extruded, self-adhesive tape for static sealing

100%-EXPANDED PTFE SELF-ADHESIVE TAPE

- SUITABLE FOR FLANGES WITH FRAGILE, CORRODED OR NEW SURFACES.
- SUITABLE FOR FOODSTUFFS AND PHARMACEUTICALS
- HIGH TENSILE STRENGTH



OPERATING PARAMETERS (NOT ASSOCIATED)

Pressure : 0 to 200 bar
 Temperature : -240 °C to 250 °C
 pH : 0 - 14

COMPOSITION

100%-pure PTFE extruded gasket with micro-fibrous structure. Self-adhesive. Withstands chemicals.

TYPES OF INDUSTRIES



FLUIDS

All types of fluids

GUIDELINES, STANDARDS AND APPROVALS



Item	Dimensions	Description
49040012	□ 10,0 x 3,0 mm	12 m
49040013	□ 14,0 x 5,0 mm	15 m
49040023	□ 17,0 x 6,0 mm	10 m
49040014	□ 20,0 x 7,0 mm	8 m
50446	□ 28,0 x 5,0 mm	10 m
49040011	□ 3,0 x 1,5 mm	15 m
72476	□ 40,0 x 5,0 mm	10 m
49040018	□ 5,0 x 2,0 mm	20 m
49040010	□ 7,0 x 2,5 mm	20 m