

Aramid

LATTYGOLD 925

General-purpose aramid sheet material for static sealing

GENERAL-PURPOSE ARAMID-BASED GASKET

- SHEET MATERIAL REINFORCED WITH AN INTERNAL STEEL WIRE MESH.
- ANTI-STICK SPECIAL GRAPHITE TREATMENT ON BOTH FACES



OPERATING PARAMETERS (NOT ASSOCIATED)

Pressure : 0 to 130 bar
Temperature : 0 °C to 440°C

COMPOSITION

Gasket material made of selected synthetic and mineral fibres bonded with a special acrylonitrile-elastomer mix, compressed to obtain sheet material. The sheet material is reinforced with an internal steel wire mesh. A special graphite coating, applied on both faces, makes disassembly operations extremely fast and minimises flange corrosion.

TYPES OF INDUSTRIES



FLUIDS

All types and non aggressive fluids

GUIDELINES, STANDARDS AND APPROVALS



Item	Dimensions	Description
21511151	1 mm	1 m x 1,5 m
34706	1 mm	1,5 m x 2 m
21571151	1,5 mm	1 m x 1,5 m
48236	1,5 mm	1,5 m x 2 m
21521151	2 mm	1 m x 1,5 m
46348	2 mm	1,5 m x 2 m
21531151	3 mm	1 m x 1,5 m
46347	3 mm	1,5 m x 2 m