


Carbon graphite packing

# LATTYGRAF T

The packing for extreme conditions: pressure - speed - temperature - ph for dynamic sealing

## HIGH SPEEDS, HIGH TEMPERATURES, CLEAN FLUIDS

- SUITABLE FOR ALL CHEMICAL FLUIDS (EXCEPT OXIDANTS)
- OUTSTANDING ELASTIC RECOVERY



### OPERATING PARAMETERS (NOT ASSOCIATED)

Pressure : 0 to 300 bar  
 Temperature : -200 °C to 600°C  
 Speed : < 35 m/s  
 pH : 0 - 14

### COMPOSITION

Packing made of 100% pure graphite continuous yarns, impregnated with a graphite mix. Very low friction coefficient, good heat dissipation, outstanding elastic recovery.

### TYPES OF INDUSTRIES



### FLUIDS

All types of non abrasive fluids, except oxidants

Item	Dimensions	Description
00100510	□ 6 mm	20 m / 0,66 Kg
00100512	□ 8 mm	15 m / 0,82 Kg
00100513	□ 10 mm	12 m / 0,96 Kg
00100514	□ 11 mm	11 m / 1,10 Kg
00100515	□ 12 mm	11 m / 1,38 Kg
00100516	□ 12,7 mm	11 m / 1,60 Kg
00100518	□ 16 mm	10 m / 2,23 Kg
00100521*	□ 20 mm	10 m / 3,63 Kg

*\* Made to order*

*The maximum temperature, pressure and speed parameters specified in this document can not be combined.*

