


Vegetable packing

# LATTYTEX 14

Packing for cold water for dynamic sealing

## PACKING FOR COLD WATER FOR DYNAMIC SEALING

- WATER APPLICATIONS UP TO 60°C




### OPERATING PARAMETERS (NOT ASSOCIATED)

Pressure : 0 to 10 bar  
Temperature : -40 °C to 60°C  
Speed : < 6 m/s  
pH : 5 - 9

### COMPOSITION

Braided packing made of cotton yarns, impregnated with a mix of tallow and mica.

### TYPES OF INDUSTRIES



### FLUIDS

All types of fluids

Item	Dimensions	Description
00100024	□ 6 mm	30 m / 1,16 Kg
00100025	□ 8 mm	15 m / 0,99 Kg
00100026	□ 10 mm	12 m / 1,30 Kg
00100027	□ 12 mm	11 m / 1,61 Kg
37635*	□ 12,7 mm	11 m / 1,93 Kg
00100028	□ 14 mm	10 m / 2,15 Kg
00100029	□ 16 mm	10 m / 2,80 Kg
34614*	□ 19 mm	10 m / 4,00 Kg
00100031	□ 20 mm	10 m / 4,15 Kg
00100032	□ 22 mm	10 m / 4,96 Kg

\* Made to order

The maximum temperature, pressure and speed parameters specified in this document can not be combined.

