

Synthetic packing

LATTYTEX 2761

Graphited packing

LOW-PRESSURE APPLICATIONS

- FOR ROTARY UNITS AND INDUSTRIAL VALVES AND FITTINGS
- LATTY-EXCLUSIVE «FILCOAT»-PROCESS



OPERATING PARAMETERS (NOT ASSOCIATED)

Pressure : 0 to 100 bar
Temperature : -50 °C to 260°C
Speed : < 15 m/s
pH : 1 - 13

COMPOSITION

Packing made of special polyacrylic yarns, each single yarn being impregnated with PTFE using our exclusive «Filcoat»-process, then re-impregnated during braiding operation in a bath consisting of graphite mixed with special lubricants.

TYPES OF INDUSTRIES



FLUIDS

Moderately aggressive fluids

Item	Dimensions	Description
00101758	□ 4 mm	47 m / 1,17 Kg
00101759	□ 5 mm	35 m / 1,29 Kg
00101760	□ 6 mm	30 m / 1,47 Kg
00101762	□ 8 mm	15 m / 1,30 Kg
00101763	□ 9,5 mm	12 m / 1,50 Kg
00101764	□ 10 mm	12 m / 1,65 Kg
00101765	□ 11 mm	11 m / 1,70 Kg
00101766	□ 12 mm	11 m / 2,21 Kg
00101767	□ 12,7 mm	11 m / 2,51 Kg
00101768	□ 14 mm	10 m / 2,60 Kg
00101769	□ 15 mm	10 m / 2,90 Kg
00101770	□ 16 mm	10 m / 3,45 Kg
00101771	□ 18 mm	10 m / 4,34 Kg
00101772	□ 19 mm	10 m / 4,58 Kg
00101773	□ 20 mm	10 m / 5,37 Kg
00101774	□ 22 mm	10 m / 6,10 Kg
00101775	□ 25,4 mm	10 m / 8,20 Kg
00101778*	□ 30 mm	10 m / 11,77 Kg

* Made exclusively on request

The maximum temperature, pressure and speed given in this document cannot be associated in any case.

