


Aramid packing

LATTYTEX 4777

General-purpose packing

FOR EVERYDAY APPLICATIONS IN ALL INDUSTRIES.

- ARAMID/STAPLE RAYON YARNS ON THE CORNERS
- POLYACRYLIC FRICTION FACES
- LATTY-EXCLUSIVE «FILCOAT»-PROCESS



OPERATING PARAMETERS (NOT ASSOCIATED)

Pressure : 0 to 60 bar
 Temperature : -50 °C to 200°C
 Speed : < 15 m/s
 pH : 3 - 11

COMPOSITION

Compound packing made of blended yarns: aramid/staple rayon yarns on the corners and polyacrylic yarns for friction faces, each single yarn being impregnated with PTFE using our exclusive «Filcoat»-process, then re-impregnated with a mix of paraffin lubricants and gelling agents during braiding operation.

TYPES OF INDUSTRIES



FLUIDS

Slurries fluids

Item	Dimensions	Description
36011	□ 6 mm	20 m / 1,11 Kg
36616*	□ 6,35 mm	20 m / 1,24 Kg
34954	□ 8 mm	15 m / 1,21 Kg
36012*	□ 9,5 mm	15 m / 1,35 Kg
34955	□ 10 mm	12 m / 1,61 Kg
34956	□ 12 mm	11 m / 2,11 Kg
34957	□ 12,7 mm	11 m / 2,38 Kg
36013	□ 14 mm	10 m / 2,65 Kg
36014	□ 16 mm	10 m / 3,51 Kg
36617	□ 18 mm	10 m / 4,20 Kg
36015	□ 19 mm	10 m / 4,80 Kg
36618	□ 20 mm	10 m / 5,00 Kg
36620	□ 25,4 mm	10 m / 8,20 Kg

* Made to order

The maximum temperature, pressure and speed parameters specified in this document can not be combined.