

PTFE packing

LATTYFLON 3206 S

Chemically inert packing for static applications

CHEMICAL INERTNESS OF PTFE IN STATIC APPLICATION.

- VERY LOW FRICTION COEFFICIENT
- EASY STEM OPERATION
- DRY PACKING



OPERATING PARAMETERS (NOT ASSOCIATED)

Pressure : 0 to 300 bar
Temperature : -200 °C to 300°C
Speed : < 5 m/s
pH : 0 - 14

COMPOSITION

Packing made of 100% PTFE silk yarns, dry packing.

TYPES OF INDUSTRIES



FLUIDS

Chemically aggressive fluids

Item	Dimensions	Description
00100250	□ 4 mm	35 m / 1,02 Kg
00100251	□ 5 mm	25 m / 1,04 Kg
00100252	□ 6 mm	20 m / 1,21 Kg
00101104*	□ 6,35 mm	20 m / 1,36 Kg
00100254	□ 8 mm	15 m / 1,55 Kg
00100255	□ 9,5 mm	12 m / 1,74 Kg
00100256	□ 10 mm	12 m / 1,94 Kg
00100258	□ 12 mm	11 m / 2,51 Kg
00100259	□ 12,7 mm	11 m / 2,80 Kg
00100260	□ 14 mm	10 m / 3,20 Kg
00100262	□ 16 mm	10 m / 4,32 Kg
00100702	□ 20 mm	10 m / 6,59 Kg
00100703*	□ 22 mm	10 m / 7,8 Kg
00100704*	□ 25,4 mm	10 m / 10 Kg

* Made to order

The maximum temperature, pressure and speed parameters specified in this document can not be combined.

0183

VALVES AND FITTINGS
INDUSTRIAL VALVES