

PTFE packing

LATTYFLON 3265 FR

Ensured reduction of friction in your industrial valves and fittings

REDUCTION OF FRICTION OF OVER 30%

- DEDICATED TO THE SPECIFIC REQUIREMENTS OF REGULATING VALVES
- CONTAINS A CORROSION INHIBITOR (EXCLUSIVE LATTY PROCESS) TO PROVIDE THE VALVE COMPONENTS DURABLE PROTECTION.
- REDUCED EFFORT FOR STEM OPERATION, VERY LOW HYSTERESIS
- LATTY-EXCLUSIVE «FILCOAT»-PROCESS



OPERATING PARAMETERS (NOT ASSOCIATED)

Pressure : 80 to 300 bar
Temperature : -100 °C to 300 °C
Speed : < 1 m/s
pH : 0 - 14

COMPOSITION

Packing consisting of a PTFE-impregnated braided core made of carbon yarns, covered with a braided sleeve of impregnated and lubricated PTFE yarns. Its elastic composite structure ensures sealing efficiency with a low tightening torque, thus allowing reduced power consumption and minimum emissions while greatly improving fluid sealing. LATTYgraf 3265 FR contains an inhibitor developed from an exclusive process to provide unlimited protection of the stem, stuffing box housing and stuffing box from corrosion over time.

TYPES OF INDUSTRIES



FLUIDS

All types of fluids

GUIDELINES, STANDARDS AND APPROVALS



Item	Dimensions	Description
900010352	□ 4 x 4 mm	35 m
900010359	□ 4,7 x 5 mm	25 m
900010353	□ 6,5 x 6,5 mm	20 m
900010350	□ 8 x 8,5 mm	15 m
900010361	□ 9,2 x 10 mm	12 m
900010354	□ 10 x 10 mm	12 m
900010355	□ 11 x 11 mm	11 m
900010356	□ 12 x 12 mm	11 m
900010362	□ 12,5 x 13,2 mm	11 m
900010357	□ 14 x 14 mm	10 m
900010358	□ 16 x 16 mm	10 m