


PTFE

LATTYFLON 94 L

Modified filled PTFE sheet for industrial use for static sealing

MODIFIED PTFE GASKET, HIGH MECHANICAL RESISTANCE

- HIGH ELASTIC RECOVERY AND LOW RELAXATION
- REDUCED PERMEABILITY, FLEXIBILITY, FOR EASIER CUTTING AND INSTALLATION
- MULTIDIRECTIONAL FIBRES WHICH PROVIDE OUTSTANDING RESISTANCE TO CREEP
- ISOTROPIC STRUCTURE



OPERATING PARAMETERS (NOT ASSOCIATED)

Pressure : 0 to 80 bar
Temperature : -210 °C to 260°C
pH : 0 - 14

COMPOSITION

Modified filled PTFE gasket. Its isotropic structure provides high resistance to creep and its elastic recovery guarantees high sealing performance.

TYPES OF INDUSTRIES



FLUIDS

All types of fluids, limitation for fluorinated gases or molten alkali metals.

GUIDELINES, STANDARDS AND APPROVALS



Item	Dimensions	Description
72477	0,5 mm	1,5 m x 1,5 m
69536	1 mm	1,5 m x 1,5 m
56306	1,5 mm	1,5 m x 1,5 m
56307	2 mm	1,5 m x 1,5 m
58754	3 mm	1,5 m x 1,5 m