

Carbon graphite packing

# LATTYGRAF 6118

Packing for valves and fittings > 250°C, medium and high-pressure steam

## APPLICATIONS FOR VALVES AND FITTINGS > 250°C

- MEDIUM AND HIGH-PRESSURE STEAM
- CONTAINS A CORROSION INHIBITOR (EXCLUSIVE LATTY PROCESS)



### OPERATING PARAMETERS (NOT ASSOCIATED)

Pressure : 0 to 300 bar  
Temperature : -200 °C to 600°C  
Speed : < 1 m/s  
pH : 0 - 14

### COMPOSITION

Packing made of an exclusive LATTY yarn - high-strength carbon fibres and Inconel wires intimately mixed - and expanded graphite yarns, then impregnated and coated with a graphite-based mix. LATTYgraf 6118 contains a corrosion inhibitor.

### TYPES OF INDUSTRIES



### FLUIDS

All types of high-temperature fluids and steam

Item	Dimensions	Description
32092**	□ 3 mm	40 m / 0,58 Kg
32093**	□ 4 mm	30 m / 0,60 Kg
32094**	□ 5 mm	20 m / 0,68 Kg
32095**	□ 6 mm	20 m / 0,98 Kg
32096**	□ 6,35 mm	20 m / 1,08 Kg
25715	□ 8 mm	15 m / 1,26 Kg
25716	□ 9,5 mm	12 m / 1,51 Kg
25717	□ 10 mm	12 m / 1,62 Kg
27754	□ 11 mm	11 m / 1,80 Kg
25718	□ 12 mm	11 m / 2,02 Kg
25719	□ 12,7 mm	11 m / 2,20 Kg
25720	□ 14 mm	10 m / 2,55 Kg
25721	□ 16 mm	10 m / 3,10 Kg
25749	□ 19 mm	10 m / 4,40 Kg

\*\* Boxes of 20 to 40 m are packed in multiples of 10 m.

The maximum temperature, pressure and speed parameters specified in this document can not be combined.

