

Carbon graphite packing

LATTYGRAF 6960

Industrial valves and fittings: high-performance expanded graphite packing

PACKING FOR INDUSTRIAL VALVES AND FITTINGS

- CONTAINS A CORROSION INHIBITOR (EXCLUSIVE LATTY PROCESS)



OPERATING PARAMETERS (NOT ASSOCIATED)

Pressure : 0 to 300 bar
 Temperature : -200 °C to 450 °C
 Speed : < 12 m/s
 pH : 0 - 14

COMPOSITION

Packing made of industrial-quality expanded graphite yarns, coated with a graphite mix. LATTYgraf 6960 contains a corrosion inhibitor to provide protection against corrosion of the stem and stuffing box housing.

TYPES OF INDUSTRIES



FLUIDS

All types of non-abrasive high-temperature fluids and steam

Item	Dimensions	Description
50647**	□ 4 mm	12 m / 0,22 Kg
50648**	□ 5 mm	12 m / 0,31 Kg
50651**	□ 6 mm	12 m / 0,44 Kg
50652**	□ 6,35 mm	12 m / 0,49 Kg
50653**	□ 8 mm	12 m / 0,80 Kg
50654	□ 9,5 mm	9 m / 0,83 Kg
50655	□ 10 mm	9 m / 0,94 Kg
50656	□ 11 mm	9 m / 1,12 Kg
50689	□ 12 mm	9 m / 1,36 Kg
50657	□ 12,7 mm	9 m / 1,49 Kg
50658	□ 14 mm	6 m / 1,26 Kg
51187	□ 15 mm	6 m / 1,36 Kg
50659	□ 16 mm	6 m / 1,4 Kg
50660	□ 18 mm	6 m / 1,74 Kg

** Boxes containing of 12 m are made of 2 lengths of 6 m each

The maximum temperature, pressure and speed parameters specified in this document can not be combined.

