


Carbon graphite packing

LATTYGRAF 6940 EF

Industrial valves and fittings: Packing to fight against fugitive emissions

ANTI-EXTRUSION PACKINGS

- REDUCED FRICTION
- FOR HIGH-PERFORMANCE AND HIGH-TEMPERATURE APPLICATIONS



OPERATING PARAMETERS (NOT ASSOCIATED)

Pressure : 0 to 400 bar
 Temperature : -200 °C to 600 °C
 Speed : < 1 m/s
 pH : 0 - 14

COMPOSITION

Packing made of expanded graphite yarns reinforced with Inconel wires, coated with a graphite-based mix incorporating an agent to improve the friction coefficient. LATTYgraf 6940 EF contains a corrosion inhibitor to provide protection against corrosion of the stem and stuffing box housing. Heat transfer and all high-temperature fluids. Note: LATTYgraf 6940 EF is recommended as anti-extrusion rings when used in conjunction with: LATTYgraf 6960, LATTYgraf EF4 or LATTYflon 3260 LM.

TYPES OF INDUSTRIES



FLUIDS

All types of high-temperature fluids and steam

GUIDELINES, STANDARDS AND APPROVALS



Item	Dimensions	Description
58549**	□ 4 mm	12 m / 0,340 Kg
62788**	□ 5 mm	12 m / 0,550 Kg
58545**	□ 6 mm	12 m / 0,690 Kg
62781**	□ 6,3 mm	12 m / 0,770 Kg
58546**	□ 8 mm	12 m / 1,210 Kg
62782	□ 9,5 mm	9 m / 1,250 Kg
58547	□ 10 mm	9 m / 1,330 Kg
62787	□ 11 mm	9 m / 1,550 Kg
62783	□ 12 mm	9 m / 1,920 Kg
62784	□ 12,7 mm	9 m / 2,020 Kg
62785	□ 14 mm	6 m / 1,590 Kg
62786	□ 16 mm	6 m / 1,980 Kg
71947	□ 18 mm	6 m / 2,48 Kg

***Boxes containing of 12 m are made of 2 lengths of 6 m each

The maximum temperature, pressure and speed parameters specified in this document can not be combined.

0173

VALVES AND FITTINGS
INDUSTRIAL VALVES